

Properties

Description

European, aniline dyed through leather. Available in 4 stock colours.

Attributes

Chrome tanned cattles hides, with a Stingray emboss pattern. Protective, water resistant finish.

Hide Size

5.0m² / 54ft²

Thickness

1.0mm +/- 0.1mm

Weight

840gsm +/- 10g

Grain Characteristics

Embossed Stingray

Finish Characteristics

Hand Tipped

Approximate Pattern Repeat

Vertical: 300mm

Horizontal: 300mm

Test Performance

Test	Test Method	Performance
Tear resistance	UNI EN ISO 3377-1	> = 40/60
Elongation	UNI EN ISO 3376	35-60% > = 12 N/mm ²
Flex resistance - 70'000 cycles	UNI EN ISO 5402	No cracks
Light Fastness	UNI EN ISO 105-B02	> = 4 / Blue Scale
Dry Rub Fastness - 800 cycles	UNI EN ISO 11640/1	> = 4 / Grey Scale
Wet Rub Fastness - 250 cycles	UNI EN ISO 11640/1	> = 4 / Grey Scale
Abrasion (moles CS10, 0.5kg 1000 cycles)	UNI EN ISO 5470-1	No abrasion
Breaking Force	(FTMS 311, Method 2031):	150lbs

Flammability

Test	Test Method	Performance
Upholstery seating (by smouldering & flaming sources)	BS 5852 part:1	Complies

Our leather is processed in conformity with REACH regulation.

Durability, Cleaning & Maintenance

Excellent. Recommended for all upholstery applications.

- Avoid placing leather in direct sunlight
- Keep the leather away from direct heat
- Dust regularly with a clean, soft, dry cloth
- Spots can be cleaned with a lightly damp cloth and mild soap
- Dry immediately after the treatment
- Do not rub. Use a light circular motion working toward the centre of the stain

Certifications



UNI 11239